

Electrical Characteristics

Module Type	M8-72-450	M8-72-455	M8-72-460
	STC	STC	STC
Maximum Power at STC (Pmp)	450	455	460
Open Circuit Voltage (Voc)	50.1	50.3	50.5
Short Circuit Current (Isc)	11.41	11.48	11.55
Maximum Power Voltage (Vmp)	41.8	42.0	42.2
Maximum Power Current (Imp)	10.77	10.84	10.91
Module Efficiency at STC(η_m)	20.7	20.9	21.2
Power Tolerance	(0,+4.99)		
Maximum System Voltage	1000 VDC		
Maximum Series Fuse Rating	20A		

STC: Irradiance 1000 W/m² module temperature 25°C AM=1.5;

Temperature Characteristics


Pmax Temperature Coefficient	-0.36 %/°C
Voc Temperature Coefficient	-0.28 %/°C
Isc Temperature Coefficient	+0.05 %/°C
Operating Temperature	-40 ~ +85 °C
Nominal Operating Cell Temperature(NOCT)	45±2 °C
Fire Rating	Class C

Mechanical Specifications


External Dimensions	2094 x 1038 x 30 mm
Weight	23.5kg
Solar Cells	PERC Mono 9BB 166x83mm (144pcs)
Front Glass	3.2 mm AR coating tempered glass, low iron
Frame	Anodized aluminium alloy
Junction Box	IP68,3 diodes
Output Cables	4.0 mm ² ,Portrait:1100mm or Customized Length
Connector	Genuine MC4 Connector /Compatible MC4 Connector
Mechanical Load	Front side 5400Pa/ Rear side 2400Pa

Packing Configuration

	2094 x 1038 x 30 mm
Container	40'HQ
Pieces per Pallet	38+38+6
Pallets per Container	11
Pieces per Container	902




I-V Curve



Product Certificates



Warranty



10 YEARS Guarantee on product material and workmanship | **25 YEARS** linear power output warranty

Made in China



M8-72-450-460W